

CONNECTOR, FEMALE, 2X2-PIN, 24 V DC FOR ET200S, INTERFACE MODULE, KP32F, PN/PN COUPLER, SPRING-LOADED TERMINALS, INTERNALLY BRIDGED, COLOR-CODED  
AMOUNT: SEE TECHNICAL DATA



General information	
Product type designation	Connector, female, 2x2-pin
Installation type/mounting	
Wall mounting/direct mounting	Yes; can be plugged into SIMATIC HMI device
Supply voltage	
Rated value (DC)	24 V; DC
Interfaces	
HMI-side interface	
• Number of pins HMI-side	2; Outgoing side jumpered internally, color-coded
Device-side interface	
• Number of pins device-side	4; Female, spring-loaded terminals 0.75 mm <sup>2</sup>
Standards, approvals, certificates	
CE mark	Yes
RoHS conformity	Yes
China RoHS compliance	Yes
Mechanics/material	
Design of housing	plastic

Dimensions	
Width	10 mm
Height	22 mm
Thickness	25 mm
Scope of supply	
Delivery quantity in pieces	10
Other	
Note:	for ET 200S, interface module, KP32F, PN-to-PN coupler
Usable in the following products	
• Product 1	<a href="#">6AV3688-3EH47-0AX0</a>
• Product 2	<a href="#">6ES7158-3AD00-0XA0</a>
• Product 3	<a href="#">6ES7158-3AD01-0XA0</a>
<b>last modified:</b>	04/03/2017